

IDROPULTRICI AD ACQUA FREDDA "Professional" COLD WATER HIGH PRESSURE WASHERS "Professional"

OPTIONAL



Caratteristiche tecniche

- Pompa volumetrica biella-manovella con tre pistoni in ceramica
- Testata ottone (mod.150)
- Valvola By-pass incorporata - Regolazione di pressione - Motore ad induzione con protezione termica
- Carrellata con dispositivo total-stop
- Aspirazione detergente in bassa pressione dal serbatoio incorporato
- Manometro

Technical characteristics

- Volumetric pump with connecting rod/crank system and three ceramic pistons
- Brass head (mod.150)
- By-pass device
- Pressure control device
- Induction motor with thermal protection
- Mounted on a trolley with total-stop device
- Low pressure detergent intake from the built-in tank
- Manometer



accessories
Pag. 12

Pag. 4

MODEL	CIAK P 150					
 N° RPM	1450 rpm					
 Max pressure	150/2200 bar/psi					
 Capacity	900 Lt./h					
 Absorbed power	4.000 watt					
 Power Supply	3-400 / 50 ph-volt / Hz					
 Max. intel temper	50 °C					

MODEL	CIAK P 150					
 Detergent Tank	4 Lt.					
 Dimensions	660X460X850 mm (LXPXH)					
 Weight	47 kg					
 Pallet	6 pz.					
 Dimensions	1200X800X X2100 m (LXPXH)					
 Euro						