



Caratteristiche tecniche

- Gruppo pompa assiale
- Testata in ottone con valvola by-pass incorporata (150/8) •
- Pistoni ceramcati (mod.150/8)
- Carrellata con dispositivo total stop
- Interruttore termico per protezione motore
- Regolatore pressione a bordo macchina
- Caldaia orizzontale a secco con pompa gasolio ad ingranaggi
- Termostato per regolazione della temperatura
- Aspirazione detergente in bassa pressione dal serbatoio incorporato
- Manometro
- Idonea per uso frequente su medie superfici.

Technical characteristics

- Axial pump group
- Brass head with By-pass device (150/8)
- Ceramic pistons (150/8)
- Mounted on a trolley with total-stop device
- Thermic switch for motor protection
- Pressure control device
- Dry horizontal boiler with diesel oil rod crank pump
- Ambient thermostat for temperature setting
- Low pressure detergent intake from the built-in tank
- Manometer
- Suitable for frequent use on medium surfaces



CE

accessories
Pag. 12

Pag. 7

MODEL	EASYJET 150/8					
 N° RPM	2800 rpm					
 Fuel pressure	150/12175 bar/psi					
 Capacity	480 Lt./h					
 Absorbed power	2.300 watt					
 Fuelconsumption	3,06 kg/h					
 PowerSupply	1-230 / 50 ph-volt / Hz					

MODEL	EASY JET 150/8					
 Max. outlet temp.	120 °C					
 Detergent tank	5 Lt.					
 Fuel tank	10,5 Lt.					
 Dimensions	980X460X760 mm (LXPXH)					
 Weight	62 kg					
 Pallet	1 pz.					
 Euro						