

IDROPULTRICI AD ACQUA CALDA "Professionale" HOT WATER HIGH PRESSURE WASHERS "Professional"



Caratteristiche tecniche

- Pompa volumetrica Biella-manovella con tre pistoni in ceramica.
- Testata in ottone
- Valvola By-pass esterna con valvola termostatica
- Motore a scoppio con avviamento elettrico
- Riduttore giri pompa - Trasmissione con pulegge e cinghie
- Alternatore di corrente con presa fissa max 2000 watt
- Termostato per impostazione temperatura
- Motore pompa e bruciatore indipendenti
- Pompa gasolio ad ingranaggi
- Caldaia verticale a secco con serpentina ad alto rendimento
- Manometro
- Aspirazione detergente in bassa pressione tramite lancia
- Serbatoio gasolio, benzina e detergente.

Technical characteristics

- Volumetric pump with connecting rod/crank system and three ceramic pistons
- Brass head
- External By-pass device
- Explosion engine with electrical start
- Revolution reduction gear
- Belt and pulley drive
- 2000 watt max power intake
- Thermostat for temperature setting
- Independent pump and burner
- Diesel oil rod crank pump
- Dry vertical boiler with steel heating coil
- Manometer
- Low pressure detergent intake using a nozzle
- Detergent, gasoline and diesel oil tank



accessories
Pag. 12

Pag. 11

MODEL	HOT POWER 200	
 N° RPM	1450 rpm	
 Fuel pressure	200-2.900 bar/psi	
 Capacity	900 Lt./h	
 Absorbed power	9.600 watt	
 Boiler fuel consumption	5,7 kg/h	
 Fuel boiler	DIESEL	
 Fuel motor	GASOLINE	

MODEL	HOT POWER 200	
 Max. outlet temp.	140 °C	
 Detergent tank	5,6 Lt.	
 Fuel tank	20 Lt.	
 Dimensions	1180X800 X990 mm (LXPXh)	
 Weight	270 kg	
 Pallet	1 pz.	
 Euro		