

IDROPULTRICI AD ACQUA FREDDA "Professional" COLD WATER HIGH PRESSURE WASHERS "Professional"

200



250



Caratteristiche tecniche

- Pompa volumetrica biella-manovella con tre pistoni in ceramica
- Testata in ottone
- Valvola By-pass esterna
- Regolazione di pressione
- Riduttore di giri motore-pompa
- Motore HONDA GX 4 tempi avviamento a strappo (mod.200-250)
- Motore YANMAR a gasolio con avviamento elettrico (mod.200 Diesel)
- Telaio tubolare verniciato con ruote pneumatiche
- Aspirazione detergente in bassa pressione
- Manometro in bagno di glicerina.

Technical characteristics

- Volumetric pump with connecting rod/crank system and three ceramic pistons
- Brass head
- External By-pass device
- Pressure control device
- Pump motor revolution reduction gear
- HONDA GX Engine with pull-start (MOD.200-250)
- Diesel oil YANMAR engine with electrical start (mod.200 Diesel)
- Painted tubular chase with pneumatic wheels
- Low pressure detergent intake
- Manometer

200 DIESEL



CE



accessories
Pag. 12

Pag. 6

CE

MODEL	POWER 200	POWER 250	POWER 200 DIESEL			
 N° RPM	1450 rpm	1560 rpm	1560 rpm			
 Max pressure	200/2.900 bar/psi	250/3.625 bar/psi	200/2.900 bar/psi			
 Capacity	900 Lt./h	960 Lt./h	960 Lt./h			
 Absorbed power	8.100 watt	9.600 watt	8.100 watt			
 Fuel consumption	GASOLINE	GASOLINE	DIESEL			
 Noise	100 dB	108 dB	108 dB			

MODEL	POWER 200	POWER 250	POWER 200 DIESEL			
 Max. inlet temper	45 °C	45 °C	45 °C			
 Dimensions	1000X720 X850 mm (LXPXH)	1000X800 X900 mm (LXPXH)	1000X800 X900 mm (LXPXH)			
 Weight	75 kg	60 kg	134 kg			
 Pallet	1 pz.	1 pz.	1 pz.			
 Euro						