

IDROPULTRICI AD ACQUA CALDA "Professionale" HOT WATER HIGH PRESSURE WASHERS "Professional"



Caratteristiche tecniche

- Pompa volumetrica biella-manovella con tre pistoni in ceramica
- Testata in ottone • Valvola By-pass esterna
- Interruttore termico per protezione motore
- Termostato per impostazione temperatura
- Motore ad induzione con protezione termica
- Motore pompa e bruciatore indipendenti
- Caldaia verticale a secco con serpentina ad alto rendimento
- Dispositivo total-stop ritardato
- Pompa gasolio ad ingranaggi
- Telaio carrellato in acciaio
- Regolazione di pressione
- Aspirazione e regolazione detergente in alta pressione
- Serbatoio gasolio e detergente
- Manometro in bagno di glicerina.

Technical characteristics

- Volumetric pump with connecting rod/crank system and three ceramic pistons
- Brass head • External By-pass device
- Thermic switch for motor protection
- Ambient thermostat for temperature setting
- Induction motor with thermal protection
- Independent pump and burner
- Dry vertical boiler with steel heating coil
- Delayed total stop device
- Diesel oil rod crank pump
- Trolley-mounted steel chase
- Pressure control device
- High-pressure detergent intake
- Detergent and diesel oil tank
- Glycerine coated manometer



accessories
Pag. 12

Pag. 9



MODEL	TWENTY 150 TOP	TWENTY 200 TOP				
 N° RPM	1450 rpm	1450 rpm				
 Max pressure	150/2175 bar/psi	200/2610 bar/psi				
 Capacity	900 Lt./h	900 Lt./h				
 Absorbed power	4.200 watt	5.700 watt				
 Fuel consumption	5,7 kg/h	5,7 kg/h				
 Power Supply	3-400 / 50 ph-volt / Hz	3-400 / 50 ph-volt / Hz				

MODEL	TWENTY 150 TOP	TWENTY 200 TOP				
 Max outlet temp.	140 °C	140 °C				
 Detergent tank	5,6 Lt.	5,6 Lt.				
 Fuel tank	30 Lt.	30 Lt.				
 Dimensions	1140X700 X940 mm (LXPXH)	1140X700 X940 mm (LXPXH)				
 Weight	145 kg	155 kg				
 Pallet	1 pz.	1 pz.				
 Euro						