

XR 1580 - XR 1690



IDROPULTRICI AD ACQUA FREDDA
COLD WATER HIGH PRESSURE WASHERS

Caratteristiche tecniche

- Gruppo pompa assiale
- Testata in ottone
- Pistoni in acciaio inox
- Dispositivo EASY START per avviamento morbido del motore
- Carrellata con dispositivo total-stop
- Aspirazione detergente tramite schiumogeno (mod.1580)
- Aspirazione detergente in bassa pressione dal serbatoio incorporato (mod.1690)
- Motore ad induzione con protezione termica (a riarmo manuale su mod.1690)
- Idonea per uso frequente su medie superfici (mod.1580)
- Idonea per uso semi professionali su medie-grandi superfici (mod.1690)

Technical characteristics

- Axial pump group
- Brass head
- Stainless steel pistons
- EASY START device
- Mounted on a trolley with total-stop device
- Foaming device (mod.1580)
- Low pressure detergent intake from the built-in tank (mod.1690)
- Induction motor with thermal protection
- Suitable for frequent use on medium surfaces (mod.1580)
- Suitable for semi-professional use on medium-large surfaces (mod.1690)



Pag. 3



XR 1580



XR 1690



MODEL	XR 1580	XR 1690
Max pressure	150/2.175 bar/psi	155/2.247 bar/psi
Capacity	480 Lt./h	540 Lt./h
Absorbed power	2.300 watt	2.700 watt
Power Supply	1-230 / 50 ph-volt / Hz	1-230 / 50 ph-volt / Hz
N° RPM	2800 rpm	2800 rpm
Detergent tank	-	1,8 Lt.

MODEL	XR 1580	XR 1690
Dimensions	370X470X940 mm (LXPXH)	370X470X940 mm (LXPXH)
Weight	21 kg	23 kg
Pallet	12 pz.	12
Dimensions	1100X950X X2000 m (LXPXH)	1100X950X X2000 m (LXPXH)
Max. intel temper	45 °C	45 °C
Euro		

